




Oblouk 90°s vnějším závitem

- Instalace bez demontáže
- Vhodné pro PE a PEX trubky
- Voda: PN16
- Materiál: PP
- Těsnění: NBR v kvalitě pro pitnou vodu
- Vnější závit: ISO 7 (kónický)
- Barva: Modrá/černá



d	R	PN	K	d	SP	GP	V	Sha	D	L	I1	I2	I3	H
(mm)	(inch)	(bar)					(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	1/2	16	158 400 357	1	60	0.046	46	91	46	19	14	41		
20	1/2	16	158 400 047	1	200	0.044	45	67	54	19	14	41		
20	3/4	16	158 400 048	1	200	0.046	45	67	54	19	15	42		
25	1/2	16	158 400 049	1	150	0.061	53	75	59	21	14	44		
25	3/4	16	158 400 050	1	150	0.067	53	75	59	21	15	46		
25	1	16	158 400 051	1	150	0.070	53	75	59	21	17	48		
32	1/2	16	158 400 052	1	120	0.096	64	87	66	23	14	49		
32	3/4	16	158 400 053	1	115	0.100	64	87	66	23	15	51		
32	1	16	158 400 054	1	100	0.109	64	87	66	23	17	53		
40	1	16	158 400 055	70	0	0.160	75	102	76	26	17	60		
40	1 1/4	16	158 400 056	70	0	0.175	75	102	75	26	20	62		
40	1 1/2	16	158 400 057	70	0	0.176	75	102	75	26	20	62		
50	1 1/4	16	158 400 058	45	0	0.305	97	119	88	30	20	70		
50	1 1/2	16	158 400 059	45	0	0.316	97	117	88	30	20	70		
63	1 1/4	16	158 400 060	25	0	0.527	114	144	104	35	20	81		
63	1 1/2	16	158 400 061	25	0	0.538	114	144	104	35	20	81		
63	2	16	158 400 062	20	0	0.562	114	144	104	35	24	85		
63	2 1/2	16	158 400 063	15	0	0.587	114	144	104	35	28	89		
75	2 1/2	16	158 400 064	12	0	0.950	135	180	133	41	28	101		
75	3	16	158 400 065	10	0	0.959	135	180	133	41	30	104		
90	3	16	158 400 066	7	0	1.512	161	207	150	44	30	116		
90	4	16	158 400 067	7	0	1.598	161	207	150	44	36	122		
110	3	16	158 400 068	4	0	2.204	185	242	175	53	30	131		
110	4	16	158 400 069	2	0	2.294	185	242	175	53	36	138		

Přeloženo z originálu výrobce