



T-kus 90° redukovaný

- Instalace bez demontáže
- Vhodné pro PE a PEX trubky
- Voda: PN16
- Materiál: PP
- Těsnění: NBR v kvalitě pro pitnou vodu
- Barva: Modrá/černá

d-d-d (mm)	PN (bar)	Kód	SP	GP	Váha (kg)
20 - 25 - 20	16	158 400 200	1	75	0.122
25 - 20 - 25	16	158 400 232	1	75	0.142
25 - 32 - 25	16	158 400 201	1	50	0.191
32 - 25 - 32	16	158 400 233	1	45	0.225
40 - 32 - 40	16	158 400 234	30	0	0.349
50 - 32 - 50	16	158 400 235	15	0	0.600
50 - 40 - 50	16	158 400 236	12	0	0.645
63 - 32 - 63	16	158 400 237	8	0	1.022
63 - 50 - 63	16	158 400 238	8	0	1.179
75 - 63 - 75	16	158 400 239	5	0	1.982
90 - 75 - 90	16	158 400 240	2	0	3.229
110 - 63 - 110	16	158 400 241	1	0	4.243
110 - 90 - 110	16	158 400 242	1	0	4.942

d-d-d (mm)	d (mm)	d1 (mm)	D (mm)	D1 (mm)	L (mm)	l1 (mm)	l2 (mm)	l4 (mm)	l3 (mm)	H (mm)
20 - 25 - 20	20	25	45	53	134	54	19	59	21	81
25 - 20 - 25	25	20	53	45	150	59	21	54	19	71
25 - 32 - 25	25	32	53	64	150	59	21	66	23	93
32 - 25 - 32	32	25	64	53	173	66	23	59	21	81
40 - 32 - 40	40	32	75	64	203	76	26	66	23	93
50 - 32 - 50	50	32	97	64	239	88	30	66	23	99
50 - 40 - 50	50	40	97	75	239	88	30	76	26	109
63 - 32 - 63	63	32	114	64	288	104	35	66	23	108
63 - 50 - 63	63	50	114	97	288	104	35	88	30	129
75 - 63 - 75	75	63	135	114	360	133	41	104	35	157
90 - 75 - 90	90	75	161	135	413	150	44	133	41	196
110 - 63 - 110	110	63	185	144	484	175	53	104	35	182
110 - 90 - 110	110	90	185	161	484	175	53	150	44	224

Přeloženo z originálu výrobce