



T-kus 90° s vnějším závitem

- Instalace bez demontáže
- Vhodné pro PE a PEX trubky
- Voda: PN16
- Materiál: PP
- Těsnění: NBR v kvalitě pro pitnou vodu
- Vnější závit: ISO 7 (kónický)
- Barva: Modrá/černá

d	R	PN	Kód	SP	GP	Váha	D	L	I1	I2	I3	H
(mm)	(inch)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
20	¾	16	158 400 202	1	120	0.076	45	134	54	19	14	41
20	¾	16	158 400 203	1	120	0.082	45	134	54	19	15	42
25	¾	16	158 400 204	1	85	0.115	53	150	59	21	14	44
25	¾	16	158 400 205	1	85	0.118	53	150	59	21	15	46
25	1	16	158 400 206	1	80	0.123	53	150	59	21	17	48
32	¾	16	158 400 207	1	60	0.180	64	173	66	23	15	51
32	1	16	158 400 208	1	55	0.191	64	173	66	21	17	53
40	¾	16	158 400 209	45	0	0.282	75	203	76	26	15	57
40	1 ¼	16	158 400 210	30	0	0.298	75	203	76	26	20	62
40	1 ½	16	158 400 211	30	0	0.304	75	203	76	26	20	62
50	¾	16	158 400 212	16	0	0.534	97	239	88	30	15	65
50	1 ¼	16	158 400 213	16	0	0.550	97	239	88	30	20	70
50	1 ½	16	158 400 214	16	0	0.558	97	239	88	30	20	70
63	1 ¼	16	158 400 215	8	0	0.978	114	288	104	35	20	81
63	1 ½	16	158 400 216	8	0	0.982	114	288	104	35	20	81
63	2	16	158 400 217	8	0	0.985	114	288	104	35	24	85
63	2 ½	16	158 400 218	8	0	1.024	114	288	104	35	28	89
75	2 ½	16	158 400 219	7	0	1.630	135	360	133	41	28	101
75	3	16	158 400 220	6	0	1.674	135	360	133	41	30	104
90	3	16	158 400 221	2	0	2.697	161	413	150	44	30	116
110	4	16	158 400 222	2	0	4.072	185	484	175	53	36	138

Přeloženo z originálu výrobce