



Zaslepovací příruba PE100 PN 2.5 bar

Provedení:

- Vyrobeno z desky
- Rozteč děr PN10

Pozn.:

- max. tlak 2,5 bar

d (mm)	DN (mm)	PN (bar)	Kód	SP	Váha (kg)	AL	D (mm)	L (mm)	D1 (mm)	D3 (mm)
63	50	2.5	700 647 886	0	0.362	4	165	15	125	18
75	65	2.5	700 647 887	0	0.487	4	185	15	145	18
90	80	2.5	700 647 888	0	0.544	8	200	15	160	18
110	100	2.5	700 647 889	0	0.643	8	220	15	180	18
125	100	2.5	700 647 890	0	0.658	8	220	15	180	18
140	125	2.5	700 647 891	0	0.842	8	250	15	210	18
160	150	2.5	700 647 892	0	1.200	8	285	20	240	22
180	150	2.5	700 647 893	0	1.350	8	285	25	240	22
200	200	2.5	700 647 894	0	1.400	8	340	25	295	22
225	200	2.5	700 647 895	0	1.450	8	340	30	295	22
250	250	2.5	700 647 896	0	2.052	12	395	30	350	22
280	250	2.5	700 647 897	0	2.380	12	395	30	350	22
315	300	2.5	700 647 898	0	2.400	12	445	40	400	22
355	350	2.5	700 647 899	0	4.400	16	515	40	460	22
400	400	2.5	700 647 900	0	5.620	16	574	45	515	26
450	500	2.5	700 647 901	0	6.120	20	670	55	620	26
500	500	2.5	700 647 902	0	7.100	20	670	60	620	26
560	600	2.5	700 647 903	0	7.650	20	780	65	725	30
630	600	2.5	700 647 904	0	8.200	20	780	75	725	30

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2021