



Koleno 45° ecoFIT PE100

Provedení:

- Konvenční svařování natupo dle DVS 2207
- Kompatibilní pro IR = infračervené (IR Plus) svařování. Zvolte svařovací parametry: PE100

d	DN	PN	SDR	FM	Kód	Váha	L	L1	e
(mm)	(mm)	(bar)				(kg)	(mm)	(mm)	(mm)
20	15	16	11	IR	753 158 606	0.007	32	24	1.9
25	20	16	11	IR	753 158 607	0.013	34	25	2.3
32	25	16	11	IR	753 158 608	0.019	36	25	2.9
40	32	16	11	IR	753 158 609	0.036	39	25	3.7
50	40	16	11	IR	753 158 610	0.059	42	26	4.6
63	50	16	11	IR	753 158 611	0.103	47	29	5.8
75	65	16	11	IR	753 158 612	0.146	49	29	6.8
90	80	16	11	IR	753 158 613	0.241	57	34	8.2
110	100	16	11	IR	753 158 614	0.442	70	43	10.0
125	100	16	11	IR	753 158 615	0.638	79	48	11.4
140	125	16	11	IR	753 158 616	0.902	88	55	12.7
160	150	16	11	IR	753 158 617	1.340	100	60	14.6
200	200	16	11	IR	753 158 619	2.612	124	75	18.2
225	200	16	11	IR	753 158 620	3.638	140	85	20.5

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2021