




Ohyb 90° ecoFIT PE100
d20-500 mm / SDR11

Provedení:

- Konvenční svařování natupo dle DVS 2207
- Kompatibilní pro IR = infračervené (IR Plus) svařování, zvolte svařovací parametry: PE100



d	DN	PN	SDR	FM	Kód	Váha	PF	L	L1	R	e
(mm)	(mm)	(bar)				(kg)		(mm)	(mm)	(mm)	(mm)
20	15	16	11	IR	753 018 706	0.007	2 68 240 006	38	23	15.00	1.9
25	20	16	11	IR	753 018 707	0.013	2 68 240 006	42	23	19.00	2.3
32	25	16	11	IR	753 018 708	0.025	2 68 240 006	46	22	24.00	2.9
40	32	16	11	IR	753 018 709	0.041	2 68 240 006	51	21	30.00	3.7
50	40	16	11	IR	753 018 710	0.065	2 68 240 006	58	21	37.00	4.6
63	50	16	11	IR	753 018 711	0.124	2 68 240 006	66	21	45.00	5.8
75	65	16	11	IR	753 018 742	0.190	2 68 240 006	75	21	71.25	6.8
90	80	16	11	IR	753 018 743	0.325	2 68 240 006	90	22	85.50	8.2
110	100	16	11	IR	753 018 744	0.590	2 68 240 006	110	25	104.50	10.0
125	100	16	11	IR	753 018 715	0.818	2 68 240 002	125	28	116.00	11.4
140	125	16	11	IR	753 018 716	1.148	2 68 240 002	140	33	131.00	12.7
160	150	16	11	IR	753 018 717	1.699	2 68 240 002	160	33	151.00	14.6
180	150	16	11	IR	753 018 718	2.394	2 68 240 002	180	33	171.00	16.4
200	200	16	11	IR	753 018 719	3.264	2 68 240 002	200	33	190.00	18.2
225	200	16	11	IR	753 018 720	4.535	2 68 240 002	220	33	210.00	20.5
250	250	16	11		753 018 621	6.713	2 68 240 002	256	48	232.00	22.7
280	250	16	11		753 018 622	9.885	2 68 240 002	286	52	263.00	25.4
315	300	16	11		753 018 623	14.158	2 68 240 002	321	48	297.00	28.6
355	350	16	11		753 018 624	18.000	2 68 240 040	345	70	330.00	32.3
400	400	16	11		753 018 625	24.020	2 68 240 040	365	70	350.00	36.3
450	450	16	11		753 018 626	35.360	2 68 240 040	425	70	400.00	40.9
500	500	16	11		753 018 627	47.370	2 68 240 040	470	90	445.00	45.5

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2021