


Pevný bod ecoFIT PE100 d63-630 mm / SDR11

Provedení:

- Konvenční svařování natupo dle DVS 2207
- Obráběný
- Kompatibilní pro IR = infračervené (IR Plus) svařování. Zvolte svařovací parametry: PE100



d	DN	PN	SDR	FM	Kód	Váha	D	L	L1	L2	L3	e
(mm)	(mm)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	50	16	11	IR	753 665 558	0.182	90	122	30	42	10	5.8
75	65	16	11	IR	753 665 559	0.265	110	122	30	42	10	6.8
90	80	16	11	IR	753 665 560	0.357	125	122	30	42	10	8.2
110	100	16	11	IR	753 665 561	0.610	140	142	30	52	15	10.0
125	100	16	11	IR	753 665 562	0.811	160	152	35	52	15	11.4
140	125	16	11	IR	753 665 563	1.068	180	162	40	52	15	12.7
160	150	16	11	IR	753 665 564	1.349	200	162	40	52	15	14.6
180	150	16	11	IR	753 665 565	2.001	225	182	45	52	20	16.4
200	200	16	11	IR	753 665 566	2.469	250	182	45	52	20	18.2
225	200	16	11	IR	753 665 567	3.438	280	192	45	52	25	20.5
250	250	16	11		753 665 568	3.858	280	212	50	62	25	22.7
280	250	16	11		753 665 569	5.217	315	222	50	62	30	25.4
315	300	16	11		753 665 570	6.627	355	222	50	62	30	28.6
355	350	16	11		753 665 571	7.731	400	192	30	62	35	32.2
400	400	16	11		753 665 572	10.890	450	212	30	72	40	36.3
450	450	16	11		753 665 573	14.775	500	232	35	72	45	40.9
500	500	16	11		753 665 574	20.268	560	252	40	72	50	45.4
560	600	16	11		753 665 575	28.608	630	282	45	82	55	50.8
630	600	16	11		753 665 576	39.129	710	302	50	82	60	57.2

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2021