




T-kus 90° redukovaný ecoFIT PE100
d63-225 mm / SDR17

Provedení:

- Konvenční svařování natupo dle DVS 2207
- Kompatibilní pro IR = infračervené (IR Plus) svařování. Zvolte svařovací parametry: PE100
- 5 bar plyn / 10 bar voda

* Redukce SDR11



	d (mm)	DN (mm)	PN (bar)	SDR	d1 (mm)	FM	Kód	Váha (kg)
*	63	50	10	17/17.6	32	IR	753 208 301	0.163
	63	50	10	17/17.6	50	IR	753 208 302	0.171
*	75	65	10	17/17.6	32	IR	753 208 303	0.231
	75	65	10	17/17.6	50	IR	753 208 304	0.250
	75	65	10	17/17.6	63	IR	753 208 305	0.263
	90	80	10	17/17.6	50	IR	753 208 307	0.411
	90	80	10	17/17.6	63	IR	753 208 308	0.329
	90	80	10	17/17.6	75	IR	753 208 309	0.339
*	110	100	10	17/17.6	32	IR	753 208 310	0.643
	110	100	10	17/17.6	50	IR	753 208 311	0.655
	110	100	10	17/17.6	63	IR	753 208 312	0.516
	110	100	10	17/17.6	75	IR	753 208 313	0.521
	110	100	10	17/17.6	90	IR	753 208 314	0.529
	160	150	10	17/17.6	63	IR	753 208 321	2.103
	160	150	10	17/17.6	75	IR	753 208 322	2.142
	160	150	10	17/17.6	90	IR	753 208 323	1.668
	160	150	10	17/17.6	110	IR	753 208 324	1.687
	225	200	10	17/17.6	90	IR	753 208 338	3.439
	225	200	10	17/17.6	110	IR	753 208 339	3.448
	225	200	10	17/17.6	160	IR	753 208 341	3.471

	d (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	e (mm)	e1 (mm)
*	63	65	70	25	25	3.6	2,9
	63	65	70	25	25	3.6	2,9
*	75	70	75	25	25	4.3	2,9
	75	70	75	25	25	4.3	2,9
	75	70	75	25	25	4.3	3,6
	90	80	85	25	25	5.1	2,9
	90	80	85	25	25	5.1	3,6
	90	80	85	25	25	5.1	4,3
*	110	90	95	30	25	6.3	2,9
	110	90	95	30	25	6.3	2,9
	110	90	95	30	25	6.3	3,6
	110	90	95	30	25	6.3	4,3
	110	90	95	30	25	6.3	5,1
	160	142	135	50	30	9.1	3,6
	160	142	135	50	30	9.1	4,3
	160	142	135	50	30	9.1	5,1
	160	142	135	50	30	9.1	6,3
	225	155	165	40	30	12.8	5,1
	225	155	165	40	30	12.8	6,3
	225	155	165	40	30	12.8	9,1

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2021