



Redukční vsuvka excentrická SYGEF Plus, PN16

Provedení:

- Materiál: **PVDF-HP**

d - d1 (mm)	FM	Kód	SP	GP	Váha (kg)	e (mm)	e1 (mm)	L (mm)
25 - 20	BCF, IR	735 938 737	1	30	0.020	1.9	1.9	80
32 - 20	BCF, IR	735 938 742	1	25	0.027	2.4	1.9	80
32 - 25	BCF, IR	735 938 741	1	25	0.030	2.4	1.9	80
40 - 20	BCF, IR	735 938 748	1	15	0.051	2.4	1.9	100
40 - 25	BCF, IR	735 938 747	1	15	0.043	2.4	1.9	100
40 - 32	BCF, IR	735 938 746	1	20	0.050	2.4	2.4	100
50 - 32	BCF, IR	735 938 753	1	20	0.068	3.0	2.4	100
50 - 40	BCF, IR	735 938 752	1	15	0.074	3.0	2.4	100
63 - 32	BCF, IR	735 938 760	1	15	0.105	3.0	2.4	100
63 - 40	BCF, IR	735 938 759	1	15	0.106	3.0	2.4	100
63 - 50	BCF, IR	735 938 758	1	15	0.097	3.0	3.0	100

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 01/2019