



Pevný bod PROGEF Standard S5/SDR11

Provedení:

- Materiál: **PP-H**
- Konvenční svařování natupo dle DVS 2207
- Kompatibilní pro infračervené (IR Plus®) svařování, zvolte svařovací parametry PP-H
- Obráběné

d	FM	Kód	SP	Váha	D	L	L1	L2	L3	e
(mm)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	IR	727 665 520	16	0.175	90	122	30	42	10	5.8
75	IR	727 665 521	14	0.254	110	122	30	42	10	6.8
90	IR	727 665 522	12	0.342	125	122	30	42	10	8.2
110	IR	727 665 523	6	0.567	140	142	30	52	15	10.0
125	IR	727 665 524	5	0.777	160	152	35	52	15	11.4
140	IR	727 665 525	3	1.023	180	162	40	52	15	12.7
160	IR	727 665 526	4	1.292	200	162	40	52	15	14.6
180	IR	727 665 527	3	1.917	225	182	45	52	20	16.4
200	IR	727 665 528	2	2.365	250	182	45	52	20	18.2
225	IR	727 665 529	1	3.294	280	192	45	52	25	20.5
250		727 665 530	1	3.695	280	212	50	62	25	22.7
280		727 665 531	1	4.997	315	222	50	62	30	25.4
315		727 665 532	1	6.348	355	222	50	62	30	28.6
355		727 665 533	1	7.405	400	192	30	62	35	32.2
400		727 665 534	1	10.432	450	212	30	72	40	36.3
450		727 665 535	1	14.153	500	232	35	72	45	40.9
500		727 665 536	1	19.414	560	252	40	72	50	45.4

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2018