



Redukce PROGEF Standard S8.3/SDR17.6 (PN6)

Provedení:

- Materiál: **PP-H**
- Konvenční svařování natupo dle DVS 2207
- Kompatibilní pro IR=Infračervené (IR Plus) svařování. Zvolte svařovací parametry: PP-H

¹ Materiál: PP-R

	d (mm)	d1 (mm)	FM	Kód	Váha (kg)	L (mm)	L1 (mm)	L2 (mm)	e (mm)	e1 (mm)
	50	40	IR	727 908 713	0.018	134	56	52	2.9	2,3
	63	40	IR	727 908 901	0.020	65	16	12	3.6	2,3
	63	50	IR	727 908 718	0.055	87	29	27	3.6	2,9
	75	40	IR	727 908 904	0.041	65	20	20	4.3	2,3
	75	50	IR	727 908 465	0.047	65	20	20	4.8	3,2
	75	63	IR	727 908 464	0.053	65	20	20	4.3	3,6
	90	63	IR	727 908 471	0.079	75	22	19	5.1	3,6
	90	75	IR	727 908 470	0.090	75	21	19	5.1	4,3
	110	63	IR	727 908 472	0.149	90	28	28	6.9	4,0
	110	75	IR	727 908 477	0.149	90	28	18	6.3	4,3
	110	90	IR	727 908 476	0.158	90	28	20	6.3	5,1
	125	110	IR	727 908 738	0.250	103	42	42	7.1	6,3
	140	110	IR	727 908 742	0.320	120	53	43	8.0	6,3
	140	125	IR	727 908 916	0.353	115	35	32	8.0	7,1
	160	110	IR	727 908 746	0.500	129	40	34	9.1	6,3
	160	140	IR	727 908 748	0.560	125	49	38	9.1	8,0
	180	90	IR	727 908 749	0.600	145	53	42	10.2	5,1
	180	110	IR	727 908 750	0.620	150	55	42	10.2	6,3
	180	125	IR	727 908 751	0.620	143	52	40	10.2	7,1
	180	140	IR	727 908 752	0.640	135	51	47	10.2	8,0
	180	160	IR	727 908 753	0.700	135	55	52	10.2	9,1
	200	160	IR	727 908 930	0.805	151	50	40	11.4	9,1
	200	180	IR	727 908 758	0.920	145	62	54	11.4	10,2
	225	110	IR	727 908 936	1.001	171	55	40	12.8	6,3
	225	160	IR	727 908 934	1.082	171	55	45	12.8	9,1
	225	180	IR	727 908 762	1.160	166	64	57	12.8	10,2
	225	200	IR	727 908 932	1.184	184	60	40	12.8	11,4
	250	160	--	727 908 765	1.530	174	64	52	14.2	9,1
	250	225	--	727 908 768	1.890	180	65	65	14.2	12,8
1	280	225	--	727 908 772	2.370	200	70	55	15.9	12,8
1	280	250	--	727 908 773	2.540	200	73	62	15.9	14,2
1	315	225	--	727 908 776	3.320	237	84	59	17.9	12,8
1	315	250	--	727 908 777	3.375	233	84	64	17.9	14,2
1	315	280	--	727 908 778	3.510	227	85	72	17.9	15,9
1	355	315	--	727 908 957	2.400	245	90	80	20.1	17,9
1	400	315	--	727 908 972	3.600	260	95	80	22.7	17,9
1	400	355	--	727 908 971	3.100	260	95	90	22.7	20,1
	450	280	--	727 908 967	6.000	230	60	70	25.5	15,9
	450	315	--	727 908 984	5.400	230	60	80	25.5	17,9
	450	355	--	727 908 988	5.000	230	60	90	25.5	20,1
	450	400	--	727 908 989	5.000	230	60	95	25.5	22,7
	500	315	--	727 908 993	8.100	230	60	80	28.4	17,9
	500	355	--	727 908 994	7.300	230	60	95	28.4	20,1
	500	400	--	727 908 998	6.700	230	60	95	28.4	22,7
	500	450	--	727 908 999	5.500	230	60	60	28.4	25,5