



T-kus 90° PROGEF Standard S8.3/SDR17.6

Provedení:

- Materiál: **PP-H**
- Konvenční svařování natupo dle DVS 2207
- Kompatibilní pro infračervené (IR Plus®) svařování, zvolte svařovací parametry PP-H

¹ Materiál: PP-R

d (mm)	FM	Kód	Váha (kg)	L (mm)	L1 (mm)	e (mm)
20	IR	727 208 506	0.011	38	24	1.9
25	IR	727 208 507	0.018	42	26	2.3
32	IR	727 208 508	0.032	46	26	2.9
40	IR	727 208 509	0.062	51	23	3.7
50	IR	727 208 510	0.105	58	22	4.6
63	IR	727 208 511	0.186	66	20	5.8
75	IR	727 208 512	0.293	75	20	6.8
90	IR	727 208 513	0.521	90	20	8.2
110	IR	727 208 514	0.928	110	20	10.0
125	IR	727 208 515	1.347	125	25	11.4
140	IR	727 208 516	1.923	140	28	12.7
160	IR	727 208 517	2.844	160	28	14.6
180	IR	727 208 518	5.475	215	94	16.4
200	IR	727 208 519	5.579	200	35	18.2
225	IR	727 208 520	7.812	220	35	20.5
250	--	727 208 521	10.400	227	68	22.7
280	--	727 208 522	15.170	267	87	25.4
315	--	727 208 523	20.330	283	86	28.6
1 355	--	727 208 524	31.100	345	105	32.2
1 400	--	727 208 525	40.900	365	105	36.3
1 450	--	727 208 526	60.300	425	135	40.9
1 500	--	727 208 527	81.900	470	155	45.4

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2018