



Reducing bush ABS metric Rp

Model:

- With solvent cement spigot metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to ABS

d	Thread Type	Size	PN	Code	SP	Weight	z	D	L
(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)
20	Rp	3/8	10	729 910 434	10	0.012	7	25	35
25	Rp	1/2	10	729 910 437	10	0.017	7	30	41
32	Rp	3/4	10	729 910 441	10	0.025	15	35	48
40	Rp	1	10	729 910 446	10	0.046	20	45	56
50	Rp	1 1/4	10	729 910 452	10	0.077	20	55	66
63	Rp	1 1/2	10	729 910 458	5	0.120	10	62	77

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>