



CONTAIN-IT Plus Leak Detection Sensor

The compact sensor unit is supplied pre-calibrated and pre-fabricated and is designed for easy installation in the monitoring room of double containment systems.

- **Output:** 3-Wire PNP (Normally Closed)
- **Operation voltage:** 10...35V DC
- **Operation current:** 0...200 mA
- **Operation temperature*:** 0°C up to 60°C (Sensor: -25°C up to 60°C)
- **Applications:** Permittivity of medium $\epsilon_r > 4,0$
- **LED-Indication:** Green/Yellow
- **International protection class:** IP 68
- **Housing material:** PA
- **Robustness Condensate:** Integrated drop guide
- **Material PVC-U:** Union (EPDM), Ball valve 546 Pro (EPDM), transparent pipe
- **Connection monitoring room:** R ½" (End-Fitting CONTAIN-IT Plus)
- **Connection flushing:** Rp ½"
- ***Optional connection monitoring room and flushing:** Only Transition Adapter NPT ½" (US-Systems)

	Description	Code	Connection	Cable length		L
				(m)	(mm)	
	Leak Detection Sensor	700 244 690	R ½"	5	246	
*	US Transition Adapter	700 244 691	NPT ½"			

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>