



COOL-FIT 2.0 Coupler

Model:

- Pre-insulated PE100 SDR11, metric
- Insulation made from GF HE foam
- Impact resistant. Color: black
- Electrofusion fitting with integrated sealing lip, for a moisture-proof and vapour tight sealing

Note:

bigger dimensions available via COOL-FIT 4.0 product range

d	D	DN	SDR	PN	Code	Weight	L	L1	z
(mm)	(mm)	(mm)		(bar)		(kg)	(mm)	(mm)	(mm)
32	75	25	11	16	738 914 108	0.092	113	36	5
40	90	32	11	16	738 914 109	0.126	121	40	3
50	90	40	11	16	738 914 110	0.160	129	44	3
63	110	50	11	16	738 914 111	0.237	137	48	3
75	125	65	11	16	738 914 112	0.339	152	55	3
90	140	80	11	16	738 914 113	0.476	166	62	4
110	160	100	11	16	738 914 114	0.778	188	72	4
140	200	125	11	16	738 914 116	1.097	210	84	3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>