




A



COOL-FIT 2.0 Transition Tee90° PE/brass With female thread Rp

Model:

- Pre-insulated, PE100, SDR11, metric
- Brass CuZn40Pb2 with female thread Rp
- Insulation made from GF HE foam
- Impact resistant. Color: black
- A: Electrofusion Fitting with integrated sealing lip, for a water and vapour tight sealing

d	D	Thread	Size	DN	PN	Code	Weight	L	L1	H	z	Type
(mm)	(mm)		(inch)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	
63	110	Rp	2	50	16	738 954 061	1.700	97	48	212	29	A
75	125	Rp	2	65	16	738 954 062	1.900	110	55	193	36	A
90	140	Rp	2	80	16	738 954 063	2.300	124	62	210	43	A
110	160	Rp	2	100	16	738 954 064	3.100	148	72	223	57	A
140	200	Rp	2	125	16	738 954 166	4.700	171	84	287	66	A

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>