



COOL-FIT 4.0 Push System, Flow control valve One free end with iFIT

Model:

- Flow control valve made of brass, impact resistant plastic and EPDM seals
- Insulation made of NBR and shells of TPE
- One side connection to COOL-FIT 4.0 Push System
- One side connection with thread
- Measuring range: 8.0 – 30.0 (l/min)
- Measuring accuracy: $\pm 10\%$ of the displayed value
- Package contents: 1x valve, 1x adaptor, 1x compression ring, 1x insulation shell

Note:

The use of antifreeze agents changes the viscosity and density of the medium. Depending on the proportion added, the actual flow rate therefore deviates from the displayed flow rate. Please contact GF for further information

d (mm)	D (mm)	Thread Type	Size (inch)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	Code	Weight (kg)
25	78	G	1	20	10	83.3	138 983 017	0.865
32	85	G	1	25	10	83.3	138 983 018	0.852

d (mm)	D (mm)	Dos (mm)	Lmax (mm)	z (mm)
25	78	100	332	180
32	85	100	332	180

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>