



CONTAIN-IT Plus T90° equal ECTFE/PE100 Connections for infrared fusion

- T 45° on request

d	D	PN	PN	SDR	Code	Weight	D1	ZA 1	ZA 2	L1	Zi 1	Zi 2
(mm)	(mm)	(bar)	(Outer Pipe)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
			(bar)									
20	50	10	16	21	737 204 206	0.378	51	105	175	40	125	195
25	50	10	16	21	737 204 207	0.386	51	105	175	40	125	195
32	63	10	16	21	737 204 208	0.683	64	120	190	48	140	210
40	75	10	16	21	737 204 209	1.130	76	145	225	60	165	245
50	90	10	10	21	737 204 210	1.524	91	170	260	66	190	280
63	110	10	10	21	737 204 211	2.560	111	210	310	77	230	330
75	125	10	10	21	737 204 212	3.721	126	225	330	87	245	350
90	140	10	10	21	737 204 213	5.607	161	265	375	107	285	395
110	160	10	10	21	737 204 214	6.685	161	275	390	107	295	410

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>