


## IR PVC-U Valve End



### Model:

- For Ball valves 546 Pro, 543 Pro, 542; Check valves 561/562; Ventilating and Bleeding valves 591/595
- For welding on IR-63 Plus and IR-110 A
- Special Clamping inserts needed on IR-63 Plus and IR-110 A
- Only use Tangit KS Cleaner (799298023)



| d    | DN   | PN    | SDR  | Code               | Weight | s    | Lmax | D1   | Bm1  | Bn1  |
|------|------|-------|------|--------------------|--------|------|------|------|------|------|
| (mm) | (mm) | (bar) |      |                    | (kg)   | (mm) | (mm) | (mm) | (mm) | (mm) |
| 20   | 15   | 16    | 9    | <b>161 498 702</b> | 0.013  | 23.0 | 37   | 38   | 22   | 28   |
| 25   | 20   | 16    | 13.6 | <b>161 498 703</b> | 0.017  | 1.9  | 40   | 44   | 22   | 30   |
| 32   | 25   | 16    | 13.6 | <b>161 498 704</b> | 0.010  | 2.4  | 40   | 53   | 22   | 34   |
| 40   | 32   | 16    | 13.6 | <b>161 498 705</b> | 0.044  | 3.0  | 43   | 65   | 22   | 35   |
| 50   | 40   | 16    | 13.6 | <b>161 498 706</b> | 0.078  | 3.7  | 51   | 77   | 22   | 42   |
| 63   | 50   | 16    | 13.6 | <b>161 498 707</b> | 0.143  | 4.7  | 59   | 99   | 26   | 49   |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>