



IR PVC-U Adaptor Rp

Model:

- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVC-U
- For welding on IR-63 Plus and IR-110 A
- Special Clamping inserts needed on IR-63 Plus and IR-110 A
- Only use Tangit KS Cleaner (799298023)

d1	DN	PN	Code	Weight	s1	Rp	Lmax	Do	Bm1
(mm)	(mm)	(bar)		(kg)	(mm)	(inch)	(mm)	(mm)	(mm)
20	15	16	721 918 434	0.014	2.3	3/8	33	25	15
25	20	16	721 918 437	0.019	1.9	1/2	39	30	15
32	25	16	721 918 441	0.030	2.4	3/4	46	35	15
40	32	16	721 918 446	0.057	3.0	1	53	45	15
50	40	16	721 918 452	0.096	3.7	1 1/4	63	55	15
63	50	16	721 918 458	0.142	4.7	1 1/2	74	62	15

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>