


IR PVC-U Adaptor Union NPT



Model:

- Union End: NPT thread
- Union Bush: IR welded spigot
- Gasket: O-ring EPDM
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVC-U
- For welding on IR-63 Plus and IR-110 A
- Special Clamping inserts needed on IR-63 Plus and IR-110 A
- Only use Tangit KS Cleaner (799298023)

d	DN	PN	s	EPDM	Weight	Lmax	z1	z2	NPT	DE	G	Bm1	P2
(mm)	(mm)	(bar)	(mm)	Code	(kg)	(mm)	(mm)	(mm)	(inch)	(mm)	(inch)	(mm)	(mm)
20	15	10	2.3	721 519 206	0.049	67	48	19	½	43	1	21	16
25	20	10	1.9	721 519 207	0.071	78	56	22	¾	51	1 1/4	21	18
32	25	10	2.4	721 519 208	0.092	80	55	25	1	58	1 1/2	21	21
40	32	10	3.0	721 519 209	0.154	90	61	29	1 ¼	72	2	21	23
50	40	10	3.7	721 519 210	0.250	99	65	34	1 ½	83	2 1/4	21	27
63	50	10	4.7	721 519 211	0.412	125	84	41	2	100	2 3/4	25	33

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>