



95

Union elbow, flat seat, ISO/EN UA1

- Supplied without sealing gaskets; a and z2 include the seal thickness as per table "Sealing Gasket Dimension".
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.
- * Inside hexagon

EN	Dim. (inch)	374 G (inch)	Black Code	Galvanised Code	SP	GP	a (mm)	c (mm)	z1 (mm)	z2 (mm)	s1 (mm)	s2 (mm)
•	3/8	3/4	770 095 103	770 095 203	0	40	52	25	15	42	*12	32
•	1/2	1	770 095 104	770 095 204	10	60	58	28	15	45	26	41
•	3/4	1 1/4	770 095 105	770 095 205	10	30	62	33	18	47	31	48
•	1	1 1/2	770 095 106	770 095 206	0	25	72	38	21	55	38	55
•	1 1/4	2	770 095 107	770 095 207	0	12	82	45	26	63	48	67
•	1 1/2	2 1/4	770 095 108	770 095 208	0	10	90	50	31	71	54	74
•	2	2 3/4	770 095 109	770 095 209	0	5	100	58	34	76	67	90

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>