



ecoFIT Bend 90° PE100 d20-500mm / SDR11

Model:

- Conventional butt-welding according to DVS 2207
- IR = Infrared-(IR Plus) compatible. Choose fusion parameters: PE100

d	DN	PN	SDR	FM	Code	Weight	Lmax	r	s1	z	Bm1
(mm)	(mm)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
20	15	16	11	IR	753 018 706	0.007	48.0	15.00	1.9	38	23
25	20	16	11	IR	753 018 707	0.013	54.5	19.00	2.3	42	23
32	25	16	11	IR	753 018 708	0.025	62.0	24.00	2.9	46	22
40	32	16	11	IR	753 018 709	0.041	71.0	30.00	3.7	51	21
50	40	16	11	IR	753 018 710	0.065	83.0	37.00	4.6	58	21
63	50	16	11	IR	753 018 711	0.124	97.5	45.00	5.8	66	21
75	65	16	11	IR	753 018 742	0.190	112.5	71.25	6.8	75	21
90	80	16	11	IR	753 018 743	0.325	135.0	85.50	8.2	90	22
110	100	16	11	IR	753 018 744	0.590	165.0	104.50	10.0	110	25
125	100	16	11	IR	753 018 745	0.999	207.5	126.00	11.4	145	34
140	125	16	11	IR	753 018 746	1.385	232.0	142.00	12.7	162	38
160	150	16	11	IR	753 018 747	2.029	263.0	162.00	14.6	183	40
180	150	16	11	IR	753 018 748	2.751	290.0	182.00	16.4	200	38
200	200	16	11	IR	753 018 749	3.729	320.0	202.00	18.2	220	40
225	200	16	11	IR	753 018 750	5.252	357.5	227.00	20.5	245	41
250	250	16	11	IR	753 018 751	7.432	405.0	252.00	22.7	280	51
280	250	16	11	IR	753 018 752	10.311	450.0	282.00	25.4	310	52
315	300	16	11	IR	753 018 753	14.722	507.5	318.00	28.6	350	61
355	350	16	11		753 018 624	18.000	523.5	330.00	32.3	346	70
400	400	16	11		753 018 625	24.020	566.1	350.00	36.3	366	70
450	450	16	11		753 018 626	35.360	651.2	400.00	40.9	426	70
500	500	16	11		753 018 627	47.370	721.3	445.00	45.5	471	90

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>