




Type B



ecoFIT adaptor for butterfly valves PE100
d355-800mm / SDR11 / jointing face: flat and metric

Model:

- For buttfusion welding according to DVS 2207
- Type B: with chamfer
- Suitable for plastic butterfly valves type **567/578/565**
- Suitable for metal butterfly valves type **038/039/044/065**
- Profile seal d355-d800: NBR, EPDM, FKM
- Pressure rating: 16 bar d355-d500
- Pressure rating: 10 bar d500-d800

Note:

*machined

d	DN	PN	SDR	Code	Weight
(mm)	(mm)	(bar)			(kg)
355	350	16	11	753 798 924	8.400
400	400	16	11	753 798 925	11.000
450	450	16	11	753 798 926	18.800
500	500	16	11	753 798 927	19.900
560	600	10	11	753 798 728	29.270
630	600	10	11	753 798 729	23.042
710	700	10	11	753 798 730	33.765
800	800	10	11	753 798 731	41.787

d	d1	d2	d3	d4	L	L1	L2	e	Type	a°
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		
355	373	430	350	284	187	70	65	33.9	B	25
400	427	482	400	320	196	70	70	38.2	B	25
450	467	533	450	360	272	105	107	43.0	B	23
500	530	585	498	400	261	105	90	47.8	B	25
560	615	685	610	458	282	60	147	50.8	B	21
630	642	685	610	515	210	60	132	57.2	B	21
710	737	800	701	581	215	20	155	64.5	B	20
800	840	905	785	655	194	18	140	72.6	B	28

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>