



L = length / Länge

ELGEF Plus Pressure tapping valve (kit) PE100 d63-250mm / SDR11 / With 360° rotatable outlet

- 10 bar Gas / 16 bar Water
- With integrated drill bit to tap live mains under pressure
- Complete with lower part and premounted PE100 coated valve piece
- The valve is closed clockwise
- Number of turns to fully open or close valve is 13 for outlet d32
- Number of turns to fully open or close valve is 28 for outlet d 40, d 50, d 63
- Spindle size (SW) 14
- 4 mm pin connectors
- Limited path fusion indicators
- Long fusion outlet
- Supplied as Kit with enclosed service line fitting (ELGEF Plus Coupler or Reducer)

d	SDR	PN	DN	d1	Code	Weight	d2	H	H1	L	z	SDR pipe
(mm)		(bar)	(mm)	(mm)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	
63	11	16	50	32	193 155 034	1.864	21	202	97	165	127	9 - 11
63	11	16	50	40	193 155 035	2.862	31	272	112	165	160	9 - 11
63	11	16	50	50	193 155 036	2.879	31	272	112	165	160	9 - 11
63	11	16	50	63	193 155 037	2.887	31	272	112	165	160	9 - 11
75	11	16	65	32	193 155 044	3.243	21	208	103	165	127	9 - 11
75	11	16	65	40	193 155 045	3.249	31	278	118	165	160	9 - 11
75	11	16	65	50	193 155 046	3.261	31	278	118	165	160	9 - 11
75	11	16	65	63	193 155 047	3.259	31	278	118	165	160	9 - 11
90	11	16	80	32	193 155 054	1.962	21	216	111	165	127	9 - 11
90	11	16	80	40	193 155 055	2.957	31	286	126	165	160	9 - 11
90	11	16	80	50	193 155 056	2.970	31	286	126	165	160	9 - 11
90	11	16	80	63	193 155 057	2.924	31	286	126	165	160	9 - 11
110	11	16	100	32	193 155 064	2.030	21	226	121	165	127	9 - 17.6
110	11	16	100	40	193 155 065	2.984	31	296	136	165	160	9 - 17.6
110	11	16	100	50	193 155 066	2.696	31	296	136	165	160	9 - 17.6
110	11	16	100	63	193 155 067	3.010	31	296	136	165	160	9 - 17.6
125	11	16	100	32	193 155 074	2.039	21	233	128	165	127	9 - 17.6
125	11	16	100	40	193 155 075	3.007	31	303	143	165	160	9 - 17.6
125	11	16	100	50	193 155 076	3.023	31	303	143	165	160	9 - 17.6
125	11	16	100	63	193 155 077	3.058	31	303	143	165	160	9 - 17.6
140	11	16	125	32	193 155 084	3.301	21	241	136	165	127	9 - 17.6
140	11	16	125	40	193 155 085	3.040	31	311	151	165	160	9 - 17.6
140	11	16	125	50	193 155 086	3.315	31	311	151	165	160	9 - 17.6
140	11	16	125	63	193 155 087	3.313	31	311	151	165	160	9 - 17.6
160	11	16	150	32	193 155 094	2.057	21	251	146	165	127	9 - 17.6
160	11	16	150	40	193 155 095	2.980	31	321	161	165	160	9 - 17.6
160	11	16	150	50	193 155 096	3.022	31	321	161	165	160	9 - 17.6
160	11	16	150	63	193 155 097	3.025	31	321	161	165	160	9 - 17.6
180	11	16	150	32	193 155 104	3.410	21	261	156	165	127	9 - 26
180	11	16	150	40	193 155 105	3.126	31	331	171	165	160	9 - 26
180	11	16	150	50	193 155 106	3.181	31	331	171	165	160	9 - 26
180	11	16	150	63	193 155 107	3.164	31	331	171	165	160	9 - 26
200	11	16	200	32	193 155 114	3.431	21	271	166	165	127	9 - 26
200	11	16	200	40	193 155 115	3.435	31	341	181	165	160	9 - 26
200	11	16	200	50	193 155 116	3.453	31	341	181	165	160	9 - 26
200	11	16	200	63	193 155 117	3.215	31	341	181	165	160	11 - 26
225	11	16	200	32	193 155 124	2.195	21	281	178	165	127	11 - 26
225	11	16	200	40	193 155 125	3.178	31	353	193	165	160	11 - 26
225	11	16	200	50	193 155 126	3.120	31	353	193	165	160	11 - 26
225	11	16	200	63	193 155 127	3.196	31	353	193	165	160	11 - 26
250	11	16	250	40	193 155 135	3.449	31	366	206	165	160	11 - 26
250	11	16	250	50	193 155 136	3.124	31	366	206	165	160	11 - 26
250	11	16	250	63	193 155 137	3.221	31	366	206	165	160	11 - 26

Data sheet

valid from: 12/8/21



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>