


Data sheet

valid from: 8/27/21



ELGEF Plus Transition elbow 90° PE/brass d32-63mm / SDR11 /Female thread Rp

- 10 bar Gas / 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Supplied as a kit



d	DN	Thread Type	Size	PN	SDR	Code	Weight	d1	L	s	SDR pipe
(mm)	(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	
32	25	Rp	1	16	11	720 100 258	0.359	44	89	40	9-11
40	32	Rp	1 ¼	16	11	720 100 259	0.525	54	100	50	9-11
50	40	Rp	1 ½	16	11	720 100 260	0.825	66	109	60	9-11
63	50	Rp	1	16	11	720 100 281	1.420	81	123	70	9-11
63	50	Rp	1 ¼	16	11	720 100 282	1.391	81	123	70	9-17.6
63	50	Rp	1 ½	16	11	720 100 283	1.305	81	123	70	9-17.6
63	50	Rp	2	16	11	720 100 261	1.165	81	123	70	9-17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>