


Data sheet

valid from: 6/25/21



ELGEF Plus Transition elbow 90° PE/brass d25-63mm / SDR11 / Loose nut G

- **PE 100 SDR 11** (ISO S5)
- 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Supplied as a kit
- Incl. flat gasket for water applications (KTW / WRAS approved)

d	DN	Thread Type	Size	PN	SDR	Code	Weight	d1	L	SDR pipe
(mm)	(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	
25	20	Rp	3/4	16	11	720 100 007	0.240	36	90	9-11
32	25	Rp	1	16	11	720 100 008	0.347	44	91	9-11
32	25	Rp	1 1/4	16	11	720 100 018	0.490	44	95	9-11
50	40	Rp	1 1/2	16	11	720 100 010	0.850	66	116	9-11
63	50	Rp	1	16	11	720 100 021	1.114	81	121	9-17.6
63	50	Rp	2	16	11	720 100 011	1.375	81	129	9-17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>