



**ELGEF Plus Transition elbow 90° PE/stainless steel  
d20-63mm / SDR11 / Female thread Rp**

- 10 bar Gas / 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Supplied as a kit

| d    | DN   | Thread Type | Size   | PN    | SDR | Code               | Weight | d1   | L    | s    | SDR pipe |
|------|------|-------------|--------|-------|-----|--------------------|--------|------|------|------|----------|
| (mm) | (mm) |             | (inch) | (bar) |     |                    | (kg)   | (mm) | (mm) | (mm) |          |
| 20   | 15   | Rp          | ½      | 16    | 11  | <b>724 100 256</b> | 0.211  | 31   | 86   | 30   | 9-11     |
| 25   | 20   | Rp          | ¾      | 16    | 11  | <b>724 100 257</b> | 0.237  | 36   | 87   | 35   | 9-11     |
| 32   | 25   | Rp          | 1      | 16    | 11  | <b>724 100 258</b> | 0.320  | 44   | 89   | 40   | 9-11     |
| 40   | 32   | Rp          | 1 ¼    | 16    | 11  | <b>724 100 259</b> | 0.545  | 54   | 100  | 50   | 9-11     |
| 50   | 40   | Rp          | 1 ½    | 16    | 11  | <b>724 100 260</b> | 0.805  | 66   | 109  | 60   | 9-11     |
| 63   | 50   | Rp          | 2      | 16    | 11  | <b>724 100 261</b> | 1.020  | 81   | 123  | 70   | 9-17.6   |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>