




**ELGEF Plus Tee 90° reduced PE100**  
**d90-d315mm / SDR17 / Long version**

**Model:**

- Pressure rating: 10 bar water / 5 bar gas
- Fittings are injection moulded



| d    | d1   | SDR | PN | DN   | Code        | Weight | z    | z1   | L    | L1   | e    | e1   |
|------|------|-----|----|------|-------------|--------|------|------|------|------|------|------|
| (mm) | (mm) |     |    | (mm) |             | (kg)   | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) |
| 90   | 50   | 17  | 10 | 80   | 753 201 827 | 0.630  | 275  | 117  | 79   | 55   | 5.4  | 3.0  |
| 90   | 63   | 17  | 10 | 80   | 753 200 829 | 0.560  | 275  | 123  | 79   | 63   | 5.4  | 3.8  |
| 90   | 75   | 17  | 10 | 80   | 753 201 855 | 0.580  | 286  | 132  | 80   | 75   | 5.4  | 4.5  |
| 110  | 63   | 17  | 10 | 100  | 753 200 828 | 1.010  | 318  | 147  | 82   | 63   | 6.6  | 3.8  |
| 110  | 75   | 17  | 10 | 100  | 753 200 131 | 1.029  | 324  | 155  | 85   | 74   | 6.6  | 4.5  |
| 110  | 90   | 17  | 10 | 100  | 753 200 832 | 0.941  | 318  | 158  | 82   | 79   | 6.6  | 5.4  |
| 125  | 90   | 17  | 10 | 100  | 753 201 132 | 1.560  | 354  | 165  | 90   | 82   | 7.4  | 5.4  |
| 125  | 110  | 17  | 10 | 100  | 753 200 133 | 1.500  | 354  | 167  | 90   | 85   | 7.4  | 6.6  |
| 160  | 63   | 17  | 10 | 150  | 753 200 834 | 2.554  | 330  | 130  | 86   | 63   | 9.5  | 3.8  |
| 160  | 75   | 17  | 10 | 150  | 753 200 880 | 1.920  | 420  | 180  | 105  | 75   | 9.5  | 4.5  |
| 160  | 90   | 17  | 10 | 150  | 753 200 836 | 1.972  | 410  | 188  | 98   | 79   | 9.5  | 5.4  |
| 160  | 110  | 17  | 10 | 150  | 753 200 837 | 2.716  | 410  | 195  | 98   | 82   | 9.5  | 6.6  |
| 180  | 90   | 17  | 10 | 150  | 753 200 881 | 2.780  | 484  | 200  | 110  | 82   | 10.7 | 5.4  |
| 180  | 110  | 17  | 10 | 150  | 753 200 150 | 4.320  | 486  | 205  | 110  | 86   | 10.7 | 6.6  |
| 180  | 160  | 17  | 10 | 150  | 753 200 882 | 5.560  | 484  | 220  | 110  | 100  | 18.7 | 9.5  |
| 200  | 63   | 17  | 10 | 200  | 753 201 873 | 6.800  | 500  | 190  | 122  | 63   | 11.9 | 3.8  |
| 200  | 90   | 17  | 10 | 200  | 753 201 874 | 6.900  | 500  | 207  | 122  | 79   | 11.9 | 5.4  |
| 200  | 110  | 17  | 10 | 200  | 753 201 875 | 5.097  | 500  | 215  | 122  | 82   | 11.9 | 6.6  |
| 200  | 160  | 17  | 10 | 200  | 753 201 876 | 7.400  | 500  | 234  | 122  | 98   | 11.9 | 9.5  |
| 225  | 75   | 17  | 10 | 200  | 753 200 839 | 7.128  | 555  | 277  | 120  | 70   | 13.4 | 4.5  |
| 225  | 90   | 17  | 10 | 200  | 753 200 840 | 4.732  | 555  | 226  | 127  | 80   | 13.4 | 5.4  |
| 225  | 110  | 17  | 10 | 200  | 753 200 841 | 4.700  | 555  | 235  | 127  | 82   | 13.4 | 6.6  |
| 225  | 160  | 17  | 10 | 200  | 753 200 842 | 5.922  | 555  | 253  | 127  | 98   | 13.4 | 9.5  |
| 225  | 180  | 17  | 10 | 200  | 753 200 843 | 7.211  | 550  | 280  | 120  | 105  | 13.4 | 10.7 |
| 250  | 110  | 17  | 10 | 250  | 753 201 878 | 8.185  | 575  | 242  | 130  | 82   | 14.8 | 6.6  |
| 250  | 160  | 17  | 10 | 250  | 753 201 879 | 9.800  | 575  | 261  | 130  | 98   | 14.8 | 9.5  |
| 315  | 110  | 17  | 10 | 300  | 753 200 851 | 15.621 | 695  | 277  | 150  | 82   | 18.7 | 6.6  |
| 315  | 160  | 17  | 10 | 300  | 753 200 852 | 12.200 | 695  | 296  | 150  | 102  | 18.7 | 9.5  |
| 315  | 200  | 17  | 10 | 300  | 753 200 152 | 17.910 | 690  | 313  | 155  | 117  | 18.7 | 11.9 |
| 315  | 225  | 17  | 10 | 300  | 753 200 153 | 16.035 | 690  | 320  | 155  | 125  | 18.7 | 13.4 |
| 315  | 250  | 17  | 10 | 300  | 753 200 854 | 15.500 | 695  | 325  | 150  | 130  | 18.7 | 14.8 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>