



ecoFIT Elbow 90° PE80
d20-40mm / SDR11 / Female thread Rp

Model:

- With fusion socket metric and parallel female thread Rp, reinforced
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Do not use thread sealing pastes that are harmful to PE
- Install with low mechanical stress and avoid large cyclic temperature changes

d	Gewindetyp	Size	DN	PN	SDR	Code	Weight	D	L	z1	z2
(mm)		(inch)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)
20	Rp	½	15	10	11	733 100 206	0.024	30	28	14	14
25	Rp	¾	20	10	11	733 100 207	0.033	35	32	16	16
32	Rp	1	25	10	11	733 100 208	0.061	44	38	20	20
40	Rp	1 ¼	32	10	11	733 100 209	0.094	54	44	24	24

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>