



PROGEF Natural Adaptor nipple Metric NPT SDR11 (PN10)

Model:

- Material: PP-R unpigmented
- With butt fusion spigot **SDR11** and NPT tapered male thread
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PP
- Install with low mechanical stress and avoid large cyclic temperature changes

d	Thread Type	Size	PN	SDR	FM	Code	Weight	L	L1	s	e
(mm)		(inch)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)
20	NPT	½	10	11	BCF, IR	728 914 106	0.013	51	28	32	1.9
25	NPT	¾	10	11	BCF, IR	728 914 107	0.017	52	28	36	2.3
32	NPT	1	10	11	BCF, IR	728 914 108	0.027	55	28	46	2.9
40	NPT	1 ¼	10	11	BCF, IR	728 914 109	0.039	58	28	55	3.7
50	NPT	1 ½	10	11	BCF, IR	728 914 110	0.054	60	28	65	4.6
63	NPT	2	10	11	BCF, IR	728 914 111	0.093	67	28	80	5.8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>