



**PROGEF Plus Outlet flange adaptor**  
**SDR11 (PN10) combined jointing face: flat and serrated**

**Model:**

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- To wafer check valves type 369
- Cleaned and double bagged

**Attention:**

- In conjunction with Outlet flange adaptors, **flange rings for socket systems** must be used.

| d    | SDR | DN   | PN    | Code               | SP | Weight | L    | L1   | L2   | D    | D1   | D2   | r    | e    |
|------|-----|------|-------|--------------------|----|--------|------|------|------|------|------|------|------|------|
| (mm) |     | (mm) | (bar) |                    |    | (kg)   | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) |
| 40   | 11  | 32   | 10    | <b>727 808 134</b> | 1  | 0.064  | 64   | 30   | 11   | 80   | 37   | 50   | 3    | 3.7  |
| 50   | 11  | 40   | 10    | <b>727 808 135</b> | 1  | 0.088  | 67   | 30   | 12   | 90   | 43   | 61   | 3    | 4.6  |
| 63   | 11  | 50   | 10    | <b>727 808 136</b> | 1  | 0.126  | 74   | 30   | 14   | 105  | 54   | 76   | 4    | 5.8  |
| 75   | 11  | 65   | 10    | <b>727 808 137</b> | 1  | 0.187  | 78   | 30   | 16   | 125  | 70   | 90   | 4    | 6.8  |
| 90   | 11  | 80   | 10    | <b>727 808 138</b> | 1  | 0.346  | 87   | 35   | 17   | 140  | 82   | 108  | 4    | 8.2  |
| 110  | 11  | 100  | 10    | <b>727 808 139</b> | 1  | 0.481  | 102  | 41   | 18   | 160  | 105  | 131  | 4    | 10.0 |
| 140  | 11  | 125  | 10    | <b>727 808 141</b> | 1  | 0.710  | 124  | 47   | 25   | 190  | 130  | 165  | 4    | 12.7 |
| 160  | 11  | 150  | 10    | <b>727 808 142</b> | 1  | 1.255  | 149  | 52   | 25   | 215  | 158  | 188  | 4    | 14.6 |
| 225  | 11  | 200  | 10    | <b>727 808 145</b> | 1  | 1.830  | 180  | 55   | 32   | 270  | 206  | 248  | 4    | 20.5 |
| 280  | 11  | 250  | 10    | <b>727 808 147</b> | 1  | 3.550  | 240  | 63   | 35   | 325  | 259  | 308  | 4    | 25.4 |
| 315  | 11  | 300  | 10    | <b>727 808 148</b> | 1  | 4.960  | 272  | 66   | 35   | 375  | 308  | 346  | 4    | 28.6 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>