



PROGEF Standard Reducer SDR17.6 (PN6)

Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- IR = Infrared welding compatible

¹ Material: PP-R

	d	d1	PN	SDR	FM	Code	Weight	L	L1	L2	e	e1
	(mm)	(mm)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
	50	40	6	17.6	IR	727 908 713	0.018	134	56	52	2.9	2,3
	63	40	6	17.6	IR	727 908 901	0.020	65	16	12	3.6	2,3
	63	50	6	17.6	IR	727 908 718	0.055	87	29	27	3.6	2,9
	75	40	6	17.6	IR	727 908 904	0.041	65	20	20	4.3	2,3
	75	50	6	17.6	IR	727 908 465	0.047	65	20	20	4.8	3,2
	75	63	6	17.6	IR	727 908 464	0.053	65	20	20	4.3	3,6
	90	63	6	17.6	IR	727 908 471	0.079	75	22	19	5.1	3,6
	90	75	6	17.6	IR	727 908 470	0.090	75	21	19	5.1	4,3
	110	63	6	17.6	IR	727 908 472	0.149	90	28	28	6.9	4,0
	110	75	6	17.6	IR	727 908 477	0.149	90	28	18	6.3	4,3
	110	90	6	17.6	IR	727 908 476	0.158	90	28	20	6.3	5,1
	125	110	6	17.6	IR	727 908 738	0.250	103	42	42	7.1	6,3
	140	110	6	17.6	IR	727 908 742	0.320	120	53	43	8.0	6,3
	140	125	6	17.6	IR	727 908 916	0.353	115	35	32	8.0	7,1
	160	110	6	17.6	IR	727 908 746	0.500	129	40	34	9.1	6,3
	160	140	6	17.6	IR	727 908 748	0.560	125	49	38	9.1	8,0
	180	90	6	17.6	IR	727 908 749	0.600	145	53	42	10.2	5,1
	180	110	6	17.6	IR	727 908 750	0.620	150	55	42	10.2	6,3
	180	125	6	17.6	IR	727 908 751	0.620	143	52	40	10.2	7,1
	180	140	6	17.6	IR	727 908 752	0.640	135	51	47	10.2	8,0
	180	160	6	17.6	IR	727 908 753	0.700	135	55	52	10.2	9,1
	200	160	6	17.6	IR	727 908 930	0.805	151	50	40	11.4	9,1
	200	180	6	17.6	IR	727 908 758	0.920	145	62	54	11.4	10,2
	225	110	6	17.6	IR	727 908 936	1.001	160	55	35	12.8	6,3
	225	160	6	17.6	IR	727 908 934	1.082	160	55	40	12.8	9,1
	225	180	6	17.6	IR	727 908 762	1.160	166	64	57	12.8	10,2
	225	200	6	17.6	IR	727 908 932	1.184	160	55	50	12.8	11,4
	250	160	6	17.6	IR	727 908 765	1.530	174	64	52	14.2	9,1
	250	225	6	17.6	IR	727 908 768	1.890	180	65	65	14.2	12,8
1	280	225	6	17.6	IR	727 908 772	2.370	200	70	55	15.9	12,8
1	280	250	6	17.6	IR	727 908 773	2.540	200	73	62	15.9	14,2
1	315	225	6	17.6	IR	727 908 776	3.320	237	84	59	17.9	12,8
1	315	250	6	17.6	IR	727 908 777	3.375	233	84	64	17.9	14,2
1	315	280	6	17.6	IR	727 908 778	3.510	227	85	72	17.9	15,9
1	355	315	6	17.6	IR	727 908 957	2.400	245	90	80	20.1	17,9
1	400	315	6	17.6	--	727 908 972	3.600	260	95	80	22.7	17,9
1	400	355	6	17.6	--	727 908 971	3.100	260	95	90	22.7	20,1
	450	280	6	17.6	--	727 908 967	6.000	230	60	70	25.5	15,9
	450	315	6	17.6	--	727 908 984	5.400	230	60	80	25.5	17,9
	450	355	6	17.6	--	727 908 988	5.000	230	60	90	25.5	20,1
	450	400	6	17.6	--	727 908 989	5.000	230	60	95	25.5	22,7
	500	315	6	17.6	--	727 908 993	8.100	230	60	80	28.4	17,9
	500	355	6	17.6	--	727 908 994	7.300	230	60	95	28.4	20,1
	500	400	6	17.6	--	727 908 998	6.700	230	60	95	28.4	22,7
	500	450	6	17.6	--	727 908 999	5.500	230	60	60	28.4	25,5

Data sheet

valid from: 12/7/22



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>