



Type A




Type B




Type C




Type A



Type B



Type C



PROGEF Standard Flange adaptor SDR17.6 (PN6) combined jointing face: flat and serrated

Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- IR- Infrared welding compatible
- Suitable for flange connections to metric (from d110 also to ANSI/ASME B16.5)
- Up to d400, suitable for butterfly valve type 567/578 and 038/039. Above use PROGEF Standard adaptor for butterfly valves SDR17.6 (d450-d500)
- Gasket: profile flange gasket EPDM No. 48 44 07, FKM No. 49 44 07

* Material: PP-R

**Material: PP-R, not suitable for butterfly valves

	d (mm)	SDR	DN (mm)	PN (bar)	FM	Code	Weight (kg)
	50	17.6	40	6	IR	727 798 210	0.077
	63	17.6	50	6	IR	727 798 211	0.116
	75	17.6	65	6	IR	727 798 787	0.204
	90	17.6	80	6	IR	727 798 788	0.273
	110	17.6	100	6	IR	727 798 789	0.361
	125	17.6	100	6	IR	727 798 215	0.386
	140	17.6	125	6	IR	727 798 216	0.597
	160	17.6	150	6	IR	727 798 217	0.669
	180	17.6	150	6	IR	727 798 218	0.630
	200	17.6	200	6	IR	727 798 219	1.268
	225	17.6	200	6	IR	727 798 220	1.330
	250	17.6	250	6	IR	727 798 421	2.130
	280	17.6	250	6	IR	727 798 222	1.785
	315	17.6	300	6	IR	727 798 423	2.499
*	355	17.6	350	6		727 798 224	4.600
*	400	17.6	400	6		727 798 225	6.100
**	450	17.6	500	6		727 798 226	12.100
**	500	17.6	500	6		727 798 227	12.700

	d (mm)	d1 (mm)	d2 (mm)	d3 (mm)	d4 (mm)	L (mm)	L1 (mm)	L2 (mm)	e (mm)	Type	a°
	50	60	88		44	62	32	12	3.0	A	
	63	75	102		55	68	38	14	3.8	A	
	75	89	122		63	80	43	16	4.5	A	
	90	105	138		78	80	42	17	5.4	A	
	110	125	158		94	80	42	18	6.6	A	
	125	132	158	114	110	82	35	25	7.4	B	25.0
	140	155	188	127	123	89	39	25	8.3	B	27.0
	160	175	212	158	138	92	47	18	9.5	C	30.0
	180	180	212		158	92	45	20	10.7	A	
	200	232	268	203	174	100	42	24	11.9	C	30.0
	225	235	268	210	196	100	42	24	13.4	C	30.0
	250	285	320	252	221	120	45	26	14.8	C	25.0
	280	291	320	265	247	120	45	35	16.6	C	30.0
	315	335	370	300	278	150	50	51	18.7	C	21.0
*	355	373	430	346	310	155	70	33	21.1	C	21.0
*	400	427	482	395	350	162	70	36	23.7	C	21.0
**	450	514	585	400	400	211	105	46	26.7	C	4.0
**	500	530	585	442	442	217	105	46	29.7	C	1.5

Data sheet

valid from: 4/29/23



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>