



PRO-FIT reducing bush PVC-U metric

Model:

- Outlet: A and B = Solvent cemented spigot in combination with reducing socket metric

d	d1	d3	PN	d2	Code	SP	Weight	z	z1	z2	L
(mm)	(mm)	(mm)	(bar)	(mm)			(kg)	(mm)	(mm)	(mm)	(mm)
10	14	12	16	8	721 910 903	10	0.003	15	15	3	27
12	16	12	16	8	721 910 905	10	0.004	18	18	6	30
12	16	16	16	10	721 910 906	10	0.004	18	18	6	30
16	20	16	16	10	721 910 908	10	0.003	21	19	7	33
16	20	16	16	12	721 910 909	10	0.004	21	19	7	33
20	25	16	16	12	721 910 910	10	0.008	25	21	9	37
20	25	20	16	16	721 910 911	10	0.008	25	23	9	39
25	32	16	16	12	721 910 912	10	0.014	30	23	11	42
25	32	20	16	16	721 910 913	10	0.015	30	26	12	44
25	32	25	16	20	721 910 914	10	0.017	30	27	11	46
32	40	20	16	16	721 910 915	10	0.025	36	28	14	50
32	40	25	16	20	721 910 916	10	0.026	36	30	14	52
32	40	32	16	25	721 910 917	10	0.031	36	33	14	55
40	50	25	16	20	721 910 918	10	0.045	44	34	18	60
40	50	32	16	25	721 910 919	10	0.052	44	37	18	63
40	50	40	16	32	721 910 920	10	0.058	44	40	18	66
50	63	32	16	25	721 910 921	5	0.092	54	42	23	73
50	63	40	16	32	721 910 922	5	0.098	54	45	23	76
50	63	50	16	40	721 910 923	5	0.111	54	49	23	80
63	75	40	16	32	721 910 924	5	0.127	62	46	24	84
63	75	50	16	40	721 910 925	5	0.139	62	50	24	88
63	75	63	16	50	721 910 926	1	0.167	62	55	24	93
75	90	50	16	40	721 910 927	10	0.224	74	56	30	100
75	90	63	16	50	721 910 928	10	0.253	74	61	30	105
75	90	75	16	63	721 910 929	10	0.265	74	68	30	112

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>