



Quick Connect Valve 700 (QC7) Swiveled end-connection: BSPP G1" (Male Thread)

Model:

- Dual interlock lever mechanism
- 360° swiveled end-connections
- Color coding: Blue for supply // Red for return
- Fluid loss: Approx 5,5cc.
- Valve body: PVDF
- Lever: PP-GF30
- Ball seat: PTFE
- O-Rings: EPDM
- Face seal: EPDM
- Protection cap

Note:

* ISO 1179-1 Flat Face Port with British Standard Pipe, Parallel: Elastomeric Seal Ring; Seal Type E.

Standards: EN ISO 9393

Option:

- Further connections on request.

	DN (mm)	Size (inch)	Di (mm)	Do (mm)	DE (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	Cv 100 (gal/min)
BSPP - MT G1" - Blue	25	1	23.0	33	70	10	570	39
BSPP - MT G1" - Red	25	1	23.0	33	70	10	570	39

	DN (mm)	EPDM Code	SP	Weight (kg)
BSPP - MT G1" - Blue	25	735 911 717		0.380
BSPP - MT G1" - Red	25	735 911 719	1	0.380

	DN (mm)	L1 (mm)	M1-1 (mm)	M2-1 (mm)	Lmax (mm)	Hmax (mm)	Wopen	Wclosed
BSPP - MT G1" - Blue	25	118.0	26.5	46	131.0	85.5	79.5	85.5
BSPP - MT G1" - Red	25	118.0	26.5	46	131.0	85.5	79.5	85.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>