



SYGEF Plus Adaptor nipple With male thread R
SDR21/PN16
High Purity clean-room product ISO Class 5 (100)

Model:

- Material: PVDF-HP
- With taper male thread
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF
- Avoid stresses when installing and large changes in temperature

d	Thread Type	Size	PN	FM	Code	Weight	L	L1	s	e	SP
(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	
20	R	½	16	BCF, IR	735 910 706	0.039	53	28	32	1.9	1
25	R	¾	16	BCF, IR	735 910 707	0.021	55	28	36	1.9	1
32	R	1	16	BCF, IR	735 910 708	0.034	57	28	46	2.4	1
40	R	1 ¼	16	BCF, IR	735 910 709	0.058	60	28	55	2.4	1
50	R	1 ½	16	BCF, IR	735 910 710	0.087	63	28	65	3.0	1
63	R	2	16	BCF, IR	735 910 711	0.118	69	29	75	3.0	1

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>