



Ultrasonic Flowmeter GF PF220 V2 Portable ultrasonic clamp-on flowmeter

- Portable design for temporary or semi-stationary use (up to 14 hours battery lifetime)
- Easy, simple & accurate flow measurement on virtually any pipe
- View measurements directly on-site with large, easy to read graphic display with backlighting
- Connect to other systems with analog, pulse & alarm outputs

Pipe Outside d	Accuracy	Communica- tion Interface	Power Supply	Data Storage & Export	Heatmeter
d13 - d115	±2% o.R. for DN100	4-20 mA, Pulse	Battery	-	-
d115 - d2000	±2% o.R. for DN100	4-20 mA, Pulse	Battery	-	-
d13 - d2000	±2% o.R. for DN100	4-20 mA, Pulse	Battery	-	-

Cable length (m)	Code	SP	Weight (kg)
2	159 300 360		
2	159 300 361		
2	159 300 362		

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.gfps.com>