



Ultrasonic Flowmeter GF U1000 V2 WHM

Ultrasonic clamp-on heatmeter (HM) with wall mounted head unit & digital communication

- Easy to install, compact, robust and reliable - designed for long-term use in industrial applications
- Accurate flow measurement on virtually any pipe
- Automatic energy calculation with integrated PT100 temperature sensors
- Ready for Industry 4.0 with various communications options. Including: Modbus, 4-20 mA, pulse & alarm output
- 'Clamp-on' flowmetering solution with external wallmount head unit
- Large, easy to read graphic display with backlighting

Pipe Outside d	Accuracy	Communication Interface	Power Supply	Data Storage & Export	Heatmeter
d22-d115	±3% of m.v. for DN100	Modbus, 4-20 mA, Pulse	24 V	-	Yes
d125-d225	±3% of m.v. for DN150	Modbus, 4-20 mA, Pulse	24 V	-	Yes

Cable length (m)	Code	SP	Weight (kg)
5	159 300 316		
5	159 300 317		

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>