



Spojka redukovaná

- Instalace bez demontáže
- Vhodné pro PE a PEX trubky
- Voda: PN16
- Materiál: PP
- Těsnění: NBR v kvalitě pro pitnou vodu
- Barva: Modrá/černá

d (mm)	d-d (mm)	PN (bar)	Kód	SP	GP	Váha (kg)
25	25 - 20	16	158 400 153	1	120	0.088
32	32 - 20	16	158 400 154	1	90	0.122
32	32 - 25	16	158 400 155	1	90	0.137
40	40 - 25	16	158 400 156	65	0	0.183
40	40 - 32	16	158 400 157	65	0	0.210
50	50 - 32	16	158 400 158	40	0	0.340
50	50 - 40	16	158 400 159	35	0	0.376
63	63 - 32	16	158 400 160	20	0	0.543
63	63 - 40	16	158 400 161	20	0	0.583
63	63 - 50	16	158 400 162	18	0	0.676
75	75 - 50	16	158 400 163	15	0	0.993
75	75 - 63	16	158 400 164	12	0	1.182
90	90 - 63	16	158 400 165	8	0	1.603
90	90 - 75	16	158 400 166	6	0	1.859
110	110 - 90	16	158 400 167	3	0	2.822

d1 (mm)	D (mm)	D1 (mm)	L (mm)	l1 (mm)	l2 (mm)	l3 (mm)	l4 (mm)
20	53	45	117	59	21	54	19
20	64	45	130	66	23	54	19
25	64	53	130	66	23	59	21
25	75	53	160	76	26	59	21
32	75	64	164	76	26	66	23
32	97	64	175	88	30	66	23
40	97	75	204	88	30	76	26
32	114	64	210	104	35	66	23
40	114	75	216	104	35	76	26
50	114	97	216	104	35	88	30
50	135	97	237	133	41	88	30
63	135	114	249	133	41	104	35
63	161	114	292	150	44	104	35
75	161	135	366	150	44	133	41
90	185	161	363	175	53	150	44

Přeloženo z originálu výrobce