



Instalační tvarovka typ P526 "Metalex" (1.4401), navařovací

- Pro použití s nerezovými trubkami
- Tloušťka Klinger C4401

Typ	DN (mm)	Vel. (inch)	Pro senzor	Kód	Váha (kg)	W (inch)	H (inch)	C (inch)
P526-2012	32	1.25	P525-2, 2S	159 000 494	0.400	1.66	2.25	1.26
P526-2015	40	1.50	P525-2, 2S	198 840 506	0.800	1.66	2.20	1.26
P526-2020	50	2.00	P525-2, 2S	159 000 495	0.550	1.66	2.17	1.26
P526-2025	65	2.50	P525-2, 2S	159 000 496	0.700	1.66	2.10	1.26
P526-2030	80	3.00	P525-2, 2S	159 000 497	0.850	1.66	2.00	1.26
P526-2040	100	4.00	P525-2, 2S	159 000 498	1.000	1.66	1.95	1.26
P526-2050	125	5.00	P525-2, 2S	159 000 499	1.150	1.66	1.83	1.26
P526-2060	150	6.00	P525-2, 2S	159 000 500	0.880	1.66	1.75	1.26
P526-2080	200	8.00	P525-2, 2S	159 000 501	0.890	1.66	1.56	1.26
P526-2100	250	10.00	P525-2, 2S	159 000 502	0.910	1.66	1.35	1.26
P526-2120	300	12.00	P525-2, 2S	159 000 503	1.750	1.66	1.15	1.26

Seřazeno z originálu výrobce

PPS Engineering, s.r.o., zastoupení Georg Fischer Piping Systems
 info@ppsengineering.cz
 www.ppsengineering.cz
 © PPS 09/2018