




SYGEF Standard Injektor typ P20

Provedení:


- Materiál: **PVDF**
- DN 10-20: BSP paralelní vnitřní závit
- DN 25-50: Nátrubek pro polyfúzní svařování metric
- DN 65-80: Hrdlo pro polyfúzní svařování metric

d (mm)	DN (mm)	PN (bar)	FKM kód	SP	Váha (kg)
16	10	10	199 041 138	0	0.184
20	15	10	199 041 139	0	0.278
25	20	10	199 041 140	0	0.476
32	25	10	199 041 141	0	0.690
40	32	10	199 041 142	0	1.100
50	40	10	199 041 143	0	1.649
63	50	10	199 041 144	0	3.340
75	65	10	199 041 145	0	3.340
90	80	10	199 041 146	0	5.500


d (mm)	H (mm)	H1 (mm)	L (mm)	L1 (mm)	L2 (mm)	G (inch)	G1 (inch)	Nejbl. inch (inch)
16		35		110	40	R ¾	R ¾	¾
20		35		110	40	R 1	R ¾	½
25		45		145	45	R 1 ¼	R ¾	¾
32	96	71	245	195		R 1 ½	R 1 ½	1
40	116	87	297	239		R 2	R 2	1 ¼
50	139	105	369	301		R 2 ¼	R 2 ¼	1 ½
63	169	128	433	351		R 2 ¾	R 2 ¾	2
75		115	388					2 ½
90		149	465					3



DN 10 – 20



DN 25 – 50



DN 65 – 80

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 10/2018