



## PROGEF Standard (PP-H) Kulový kohout typ 127 24 V S ručním nouzovým ovládním S hrdly pro polyfúzní svařování metric

### Provedení:

- X<sup>1</sup> - 2024
- P<sup>1</sup> - 2024
- 2024
- V<sup>1</sup> - 2024
- Q<sup>1</sup> - 2024

### Možnosti:

- 2024
- X<sup>1</sup> - 2024

d (mm)	DN (mm)	PN (bar)	kv-hodnota (Δp=1 bar) (L/min)	EPDM kód	Váha (kg)	FPM kód	Váha (kg)
16	10	10	70	199 127 562	2.100	199 127 572	2.100
20	15	10	185	199 127 563	2.100	199 127 573	2.096
25	20	10	350	199 127 564	2.200	199 127 574	2.200
32	25	10	700	199 127 565	2.245	199 127 575	2.300
40	32	10	1000	199 127 566	2.600	199 127 576	2.600
50	40	10	1600	199 127 567	3.000	199 127 577	3.000
63	50	10	3100	199 127 568	3.800	199 127 578	3.800

d (mm)	D (mm)	H (mm)	H1 (mm)	H2 (mm)	H3 (mm)	H5 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	L6 (mm)	L7 (mm)	L8 (mm)
16	50	200	27	64	64	137	110	161	56	130	25	77	83	122	33
20	50	200	27	64	64	137	120	161	56	130	25	77	83	122	33
25	58	209	30	73	64	137	139	161	65	150	25	77	83	122	33
32	68	209	36	73	64	137	156	161	71	160	25	77	83	122	33
40	84	220	44	84	64	137	170	161	85	180	45	77	83	122	33
50	97	220	51	84	64	137	190	161	89	200	45	77	83	122	33
63	124	243	64	106	64	137	220	161	101	230	45	77	83	122	33

d (mm)	Nejbl. inch (inch)
16	3/8
20	1/2
25	3/4
32	1
40	1 1/4
50	1 1/2
63	2

