



Pevný bod PROGEF Standard S8.3/SDR17.6

Provedení:

- Materiál: **PP-H**
- Kompatibilní pro infračervené (IR Plus®) svařování, zvolte svařovací parametry PP-H
- Konvenční svařování natupo dle DVS 2207
- Obráběné

d (mm)	FM	Kód	SP	Váha (kg)	D (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	e (mm)
63	IR	727 665 539	16	0.138	90	122	30	42	10	3.8
75	IR	727 665 540	14	0.203	110	122	30	42	10	4.5
90	IR	727 665 541	12	0.267	125	122	30	42	10	5.4
110	IR	727 665 542	6	0.438	140	142	30	52	15	6.6
125	IR	727 665 543	5	0.592	160	152	35	52	15	7.4
140	IR	727 665 544	3	0.781	180	162	40	52	15	8.3
160	IR	727 665 545	4	0.971	200	162	40	52	15	9.5
180	IR	727 665 546	3	1.464	225	182	45	52	20	10.7
200	IR	727 665 547	2	1.808	250	182	45	52	20	11.9
225	IR	727 665 548	1	2.549	280	192	45	52	25	13.4
250		727 665 549	1	2.678	280	212	50	62	25	14.8
280		727 665 550	1	3.668	315	222	50	62	30	16.6
315		727 665 551	1	4.666	355	222	50	62	30	18.7
355		727 665 552	1	5.567	400	192	30	62	35	21.1
400		727 665 553	1	7.835	450	212	30	72	40	23.7
450		727 665 554	1	10.552	500	232	35	72	45	26.7
500		727 665 555	1	14.608	560	252	40	72	50	29.7

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2018