



úfci VYbřGMř 9: 'D'i gřft ?A 'Vř řřG8 F&%#DB%

Dřcj YXYbř

- Materiál: **DJ8**: I<D
- Vyhovující FDA
- d75, d90 a d100 s pilovým závitem
- Dbejte prosím instalačních pokynů

d (mm)	PN (bar)	FM?QX	SP	GP	řřjz\ U (kg)
20	16	BCF, IR	735 528 626	1	30	0.082
25	16	BCF, IR	735 528 627	1	20	0.123
32	16	BCF, IR	735 528 628	1	15	0.166
40	16	BCF, IR	735 528 629	1	20	0.263
50	16	BCF, IR	735 528 630	1	6	0.372
63	16	BCF, IR	735 528 631	1	12	0.463
75	16	BCF, IR	735 528 637	1	8	0.740
90	16	BCF, IR	735 528 638	1	8	0.798
110	16	BCF, IR	735 528 639	1	5	1.020

d (mm)	G (R/Rp BS řřjz\ U (inch)	e (mm)	D (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)
20	1	1.9	43	106	53	53	25	37
25	1 1/4	1.9	53	112	56	56	25	38
32	1 1/2	2.4	60	118	59	59	25	40
40	2	2.4	74	124	62	62	25	41
50	2 1/4	3.0	82	130	65	65	25	43
63	2 3/4	3.0	100	136	68	68	25	44
75	S 107.5 x 3.6	3.6	133	132	66	66	24	34
90	S 107.5 x 3.6	4.3	133	130	65	65	24	48
110	S 127.5 x 3.6	5.3	155	130	65	65	25	45

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 12/2018