



O-kroužek SF

Provedení:

- **Bez silikonu** (SF/silicone free), vhodné pro distribuci barev
- Tvrdost cca 65° Shore
- Pro lemové nákržky, těsnící plocha s drážkou pro O-kroužek
- Dvojitě baleno, 2 ks v balení

d (mm)	DN (mm)	EPDM kód	SP	Váha (kg)	FKM kód	SP	Váha (kg)	D (mm)	D1 (mm)	D2 (mm)
16	10	748 413 000	2	0.002	749 413 000	2	0.002	26	19	3.53
20	15	748 413 001	2	0.002	749 413 001	2	0.002	30	23	3.53
25	20	748 413 007	1	0.002	749 413 007	1	0.002	35	28	3.53
32	25	748 413 002	2	0.002	749 413 002	2	0.003	43	36	3.53
40	32	748 413 003	2	0.004	749 413 003	2	0.007	55	44	5.34
50	40	748 413 012	2	0.005	749 413 012	2	0.008	64	53	5.34
63	50	748 413 013	2	0.006	749 413 013	2	0.011	80	69	5.34
75	65	748 413 014	2	0.007	749 413 014	2	0.012	93	82	5.34
90	80	748 413 015	2	0.008	749 413 015	2	0.015	112	101	5.34
110	100	748 413 016	2	0.016	749 413 016	2	0.031	134	120	6.99
125	100	748 413 017	2	0.018	749 413 017	2	0.036	149	136	6.99
140	125	748 413 018	2	0.020	749 413 018	2	0.039	166	152	6.99
160	150	748 413 019	2	0.025	749 413 019	2	0.047	191	177	6.99
200	200	748 413 163	2	0.030	749 413 163	2	0.056	136	222	6.99
225	200	748 413 022	2	0.060	749 413 022	2	0.060	255	241	6.99
250	250	748 413 182	2	0.090	749 413 182	2	0.100	280	266	6.99
280	250	748 413 173	2	0.144	749 413 173	2	0.144	305	292	6.99
315	300	748 413 174	2	0.051	749 413 174	2	0.051	356	342	6.99

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 01/2019