



## Ohyb 90° ecoFIT SDR11

### Model:

- Materiál: **PE100**
- Konvenční svařování natupo dleDVS 2207
- Kompatibilní pro infračervené (IR Plus) svařování, zvolte svařovací parametry PE100

d (mm)	FM	Kód	Váha (kg)	PF	L (mm)	L1 (mm)	R (mm)	e (mm)
20	IR	<b>753 018 706</b>	0.007	2 68 240 006	38	23	15.00	1.9
25	IR	<b>753 018 707</b>	0.013	2 68 240 006	42	23	19.00	2.3
32	IR	<b>753 018 708</b>	0.025	2 68 240 006	46	22	24.00	2.9
40	IR	<b>753 018 709</b>	0.041	2 68 240 006	51	21	30.00	3.7
50	IR	<b>753 018 710</b>	0.065	2 68 240 006	58	21	37.00	4.6
63	IR	<b>753 018 711</b>	0.124	2 68 240 006	66	21	45.00	5.8
75	IR	<b>753 018 742</b>	0.190	2 68 240 006	75	21	71.25	6.8
90	IR	<b>753 018 743</b>	0.325	2 68 240 006	90	22	85.50	8.2
110	IR	<b>753 018 744</b>	0.590	2 68 240 006	110	25	104.50	10.0
125	IR	<b>753 018 715</b>	0.818	2 68 240 002	125	28	116.00	11.4
140	IR	<b>753 018 716</b>	1.148	2 68 240 002	140	33	131.00	12.7
160	IR	<b>753 018 717</b>	1.699	2 68 240 002	160	33	151.00	14.6
180	IR	<b>753 018 718</b>	2.394	2 68 240 002	180	33	171.00	16.4
200	IR	<b>753 018 719</b>	3.264	2 68 240 002	200	33	190.00	18.2
225	IR	<b>753 018 720</b>	4.535	2 68 240 002	220	33	210.00	20.5
250		<b>753 018 621</b>	6.713	2 68 240 002	256	48	232.00	22.7
280		<b>753 018 622</b>	9.885	2 68 240 002	286	52	263.00	25.4
315		<b>753 018 623</b>	14.158	2 68 240 002	321	48	297.00	28.6
355		<b>753 018 624</b>	18.000	2 68 240 040	345	70	330.00	32.3
400		<b>753 018 625</b>	24.020	2 68 240 040	365	70	350.00	36.3
450		<b>753 018 626</b>	35.360	2 68 240 040	425	70	400.00	40.9
500		<b>753 018 627</b>	47.370	2 68 240 040	470	90	445.00	45.5

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 01/2019